

Citrix SD-WAN (formerly NetScaler SD-WAN) increases the performance and reliability of traditional enterprise applications, SaaS applications, and virtual desktops over any network while simplifying the branch network.



Why Citrix SD-WAN

- Maintain high performance for mission-critical applications, even when a network link fails
- Improve the virtual desktop experience to branch-office and mobile users, and accelerate traditional enterprise applications
- Provides quality of service within a single HDX session for improved user experience
- Expand WAN capacity with low-cost broadband connections, while maintaining MPLS-level quality and reliability
- Support cloud migration with integrated security to protect enterprise data
- Simplify IT with integrated routing, firewall and WAN optimization to reduce network footprint
- Secure data across the WAN and to the cloud with strong encryption, application-level security policies and data segmentation
- Gain visibility into application delivery in order to proactively manage the user experience
- See the quality of your users' experience at a glance, and shorten the time to troubleshoot with the HDX QoE dashboard

Citrix SD-WAN features

Migrating apps to the cloud

Citrix SD-WAN contains an integrated database and deep packet inspection to identify applications, including individual SaaS applications, and intelligently steer traffic from the branch to the internet, cloud, or SaaS. SD-WAN provides the ability to route traffic from the branch to the internet via a secure web gateway, which provides cloud-based security including firewall, URL filtering, and usage accounting. SD-WAN builds secure and reliable connections to the cloud to provide a WAN-like experience similar to the data center. For a hybrid multi-cloud scenario, Citrix hosts SD-WAN appliances in Equinix and uses their cloud exchange to provide automatic traffic routing and failover to a multi-cloud environment.

WAN virtualization for WAN efficiency

Citrix SD-WAN creates a reliable WAN from diverse network links, including MPLS, broadband, and wireless, continuously measuring and monitoring each link for loss, latency, jitter, and congestion. Link outages and errors are mitigated by Citrix SD-WAN's ability to move traffic off poor-performing links without impact to the applications, resulting in predictable and consistent performance. Mission-critical applications are always routed across the paths with the fastest transit time. Real-time application traffic can be duplicated to guarantee no loss. And traffic from high-bandwidth applications can be balanced across multiple links to provide high performance for large file transfers.

Application QoS for assured delivery

Citrix SD-WAN identifies applications through deep packet inspection technology that results in the industry's best accuracy granularity. Application and application elements can be grouped into different categories with different priorities and bandwidths. With the granular application awareness combined with network intelligence, the platform can ensure that critical applications receive priority and are routed across the highest-quality link. Lower-quality links are used for lower-priority applications that can tolerate higher latency. The Citrix SD-WAN endpoints also communicate with each other on congestion conditions, allowing sending devices to adjust transmission rates to match network capacity.

Dynamic routing for branch simplification

Citrix SD-WAN provides an alternative to the legacy branch router, enabling a simpler branch network with lower infrastructure and support costs. Multiple overlay routed networks can be software-defined, with separate policies and security rules applied to each. With dynamic routing, Citrix SD-WAN can participate in your routing topology in overlay mode for easy network insertion or operate in edge mode for a streamlined branch network with assured application delivery.

Integrated firewall for complete security

Citrix SD-WAN brings strong data protection to the network, from link layer security to a stateful firewall function. The firewall integrates with the application QoS to allow security policies to be centrally defined by application or application element, allowing you to limit or reject traffic by applications or application elements. Citrix SD-WAN also allows users to be segmented into different zones, allowing different policies to be applied per zone. Finally, Citrix SD-WAN provides strong encryption as data crosses public and private networks while easily integrating with cloud web gateways. Citrix SD-WAN can redirect internet traffic to a secure web gateway for next-generation firewall by creation of IPsec tunnels from the branch to Palo Alto's GlobalProtect cloud service. This reduces the need to deploy firewalls at the branches.

Application and WAN optimization usability and bandwidth efficiency

Through features such as TCP flow control, data compression, de-duplication, and protocol optimization, Citrix SD-WAN can improve the end-user experience as well as provide a reduction in WAN bandwidth expenses. And with video usage on the rise, Citrix SD-WAN can optimize video delivery within Citrix Virtual Desktop environments as well as for popular websites and internal video content repositories.

Management and visibility for centralized policies

To ensure great user experiences, enterprise IT must be able to quickly and easily deploy new sites on the network, easily define network and application policies, and identify the sources of problems in application delivery. Citrix SD-WAN allows centralized policy definition across all network services and zero touch deployment, radically simplifying the time and effort to turn up a new location on the WAN. Automatic bandwidth detection and adaptive bandwidth control simplifies the detection of WAN and provides detailed reporting on the true bandwidth available on each link over time. Through its integration with Citrix Application Delivery Management (formerly Citrix Management and Analytics System), Citrix SD-WAN monitors how well virtual applications are being delivered to users in the branch.

Standard Edition appliances

| Appliance | 5100 SE | | | | 4100 SE | | |
|---|---------------------------------|--------------|--------------|--------------|--------------|-------------|--------------|
| Model | 5100-4000-SE | 5100-5000-SE | 5100-6000-SE | | 4100-2000-SE | | 4100-3000-SE |
| Total encrypted throughput ¹ | 8 Gbps | 10 Gbps | 12 Gbps | | 4 Gbps | | 6 Gbps |
| Max virtual paths (static/dynamic) | 550/32 | 550/32 | 550/32 | | 550/32 | | 550/32 |
| Appliance | 2100 SE | | | | 1100 SE | | |
| Model | 2100-0300-SE | 2100-0500-SE | 2100-1000-SE | 2100-2000-SE | 1100-200-SE | 1100-300-SE | 1100-500-SE |
| Total encrypted throughput ¹ | 600 Mbps | 1 Gbps | 2 Gbps | 4 Gbps | 400 Mbps | 600 Mbps | 1 Gbps |
| Max virtual paths (static/dynamic) | 256/32 | 256/32 | 256/32 | 256/32 | 64/32 | 64/32 | 64/32 |
| Appliance | 1000 SE | | | 410 SE | | | |
| Model | 1000-020-SE | 1000-050-SE | 1000-100-SE | 410-050-SE | 410-100-SE | 410-200-SE | 410-300-SE |
| Total encrypted throughput ¹ | 40 Mbps | 100 Mbps | 200 Mbps | 100 Mbps | 200 Mbps | 400 Mbps | 600 Mbps |
| Max virtual paths (static/dynamic) | 16/8 | 16/8 | 16/8 | 24/8 | 24/8 | 24/8 | 24/8 |
| Appliance | 210 SE / 210 LTE SE (R1/R2/RC) | | | | | | |
| Model | 210-020-SE | | 210-050-SE | | 210-100-SE | | 210-200-SE |
| Total encrypted throughput ¹ | 40 Mbps | | 100 Mbps | | 200 Mbps | | 400 Mbps |
| Max virtual paths (static/dynamic) | 16/4 | | 16/4 | | 16/4 | | 16/4 |

Standard Edition virtual and cloud appliances

| Appliance | VPX SE | | | | | |
|---|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Model | VPX-020-SE | VPX-050-SE | VPX-100-SE | VPX-200-SE | VPX-500-SE | VPX-1000-SE |
| Total encrypted throughput ¹ | 40 Mbps | 100 Mbps | 200 Mbps | 400 Mbps | 1 Gbps | 2 Gbps |
| Max virtual paths | 8 | 16 | 16 | 16 | 16 | 16 |
| Hypervisor support ² | | | | | | |
| Citrix Hypervisor | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 |
| VMware | ESX/ESXi 5.5 & 6.0 | ESX/ESXi 5.5 & 6.0 | ESX/ESXi 5.5 & 6.0 | ESXi6.0 | ESXi6.0 | ESXi6.0 |
| HyperV | 2012 R2 | 2012 R2 | 2012 R2 | 2012 R2 | 2012 R2 | 2012 R2 |
| KVM | Ubuntu 16.04 | Ubuntu 16.04 | Ubuntu 16.04 | Ubuntu 16.04 | Ubuntu 16.04 | Ubuntu 16.04 |
| Processor | Dual Core Intel VTx2 | Dual Core Intel VTx2 | Dual Core Intel VTx2 | Quad Core Intel VTx2 | Quad Core Intel VTx2 | Quad Core Intel VTx2 |
| Memory | 4 GB | 4 GB | 4 GB | 4GB | 8GB | 8GB |
| Virtual CPU | 2 vCPU @ 2.7 Ghz | 2 vCPU @ 2.7 Ghz | 2 vCPU @ 2.7 Ghz | 4vCPU @ 2.7GHz | 8vCPU @ 2.7GHz | 8vCPU @ 3.0GHz |
| Cloud Support ³ | | | | | | |
| AWS | m4.2xlarge | m4.2xlarge | m4.2xlarge | m4.2xlarge | c4.2xlarge | c4.4xlarge |
| Azure | D3_v2 | D3_v2 | D3_v2 | D3_v2 | D3_v2 | D4_v2 |
| Appliance | VPX-L SE | | | | | |
| Model | VPX-L 020-SE | VPX-L 050-SE | VPX-L 100-SE | VPX-L 200-SE | VPX-L 500-SE | VPX-L 1000-SE |
| Total encrypted throughput ¹ | 40 Mbps | 100 Mbps | 200 Mbps | 400 Mbps | 1 Gbps | 2 Gbps |
| Max virtual paths | 128 | 128 | 128 | 128 | 256 | 256 |
| Hypervisor support ² | | | | | | |
| Citrix Hypervisor | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 | Citrix Hypervisor 6.5 SP1 |
| VMware | ESX/ESXi 5.5 & 6.0 | ESX/ESXi 5.5 & 6.0 | ESX/ESXi 5.5 & 6.0 | ESXi6.0 | ESXi6.0 | ESXi6.0 |

¹Total encrypted throughput refers to total amount of bandwidth that the appliance model is licensed for, both upstream and downstream, and is based on AES-128 encryption.

²The VPX images are qualified to run on Intel processors only.

Appliance (cont')
VPX-L SE

| | | | | | | |
|----------------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| HyperV | 2012 R2 | 2012 R2 | 2012 R2 | 2012 R2 | 2012 R2 | 2012 R2 |
| KVM | Ubuntu 16.04 | Ubuntu 16.04 | Ubuntu 16.04 | Ubuntu 16.04 | Ubuntu 16.04 | Ubuntu 16.04 |
| Memory | 16 GB | 16 GB | 16 GB | 16 GB | 16 GB | 16 GB |
| Virtual CPU | 16v CPU @ 2.7 GHz | 16v CPU @ 2.7 GHz | 16v CPU @ 2.7 GHz | 16v CPU @ 2.7 GHz | 16v CPU @ 2.7 GHz | 16v CPU @ 2.7 GHz |
| HDD | 250 GB | 250 GB | 250 GB | 250 GB | 250 GB | 250 GB |
| Cloud Support ³ | | | | | | |
| AWS | m4.4xlarge | m4.4xlarge | m4.4xlarge | m4.4xlarge | m4.4xlarge | m4.4xlarge |
| Azure | F8 | F8 | F8 | F8 | F8 | F16 |

Software features

| | |
|--------------------|---|
| Deployment | In-line overlay, one-armed overlay, edge gateway, cloud |
| Path assignment | Per-packet, packet load balancing, packet duplication, by application |
| QoS | Scheduling, shaping, classification, remarking |
| Routing | eBGP, iBGP, OSPF, static, multicast |
| Security | L4-7 application firewall, NAT, secure web gateway connectivity, FIPS compliant |
| Layer 2 | VLAN (802.1Q), bridging, SVI, PPPoE |
| Tunnel Interfaces | GRE, IPSec, Citrix virtual path |
| Network Encryption | 128 bit AES, 256 bit AES, IPSec |
| Authentication | Local database, RADIUS, TACACS+ |
| Manageability | CLI, SNMP V3, DHCP Server/Relay/Client, DNS Forwarder, syslog, NetFlow, IPFIX, REST API |
| Configuration | Zero Touch Deployment service, GUI, customizable dashboards and templates, REST API |

Premium Edition appliances

| Appliance | 2100-PE | | | 1100-PE | | |
|---|-------------|-------------|--------------|-------------|-------------|-------------|
| Model | 2100-300-PE | 2100-500-PE | 2100-1000-PE | 1100-200-PE | 1100-300-PE | 1100-500-PE |
| Total encrypted throughput ⁴ | 600 Mbps | 1 Gbps | 2 Gbps | 400 Mbps | 600 Mbps | 1 Gbps |
| Maximum virtual paths (static/dynamic) | 256/32 | 256/32 | 256/32 | 64/32 | 64/32 | 64/32 |
| Optimized application capacity ^{5,6} | 50 Mbps | 100 Mbps | 100 Mbps | 10 Mbps | 20 Mbps | 50 Mbps |
| Maximum HDX CCUs ⁷ | 300 | 300 | 300 | 100 | 300 | 300 |
| Maximum accelerated TCP sessions ⁸ | 20,000 | 20,000 | 20,000 | 10,000 | 10,000 | 10,000 |

| Appliance | 1000-PE | | | |
|---|-------------|-------------|-------------|-------------|
| Model | 1000-010-PE | 1000-020-PE | 1000-050-PE | 1000-100-PE |
| Total encrypted throughput ⁴ | 20 Mbps | 40 Mbps | 100 Mbps | 200 Mbps |
| Maximum virtual paths | 16/8 | 16/8 | 16/8 | 16/8 |
| Optimized application capacity ^{5,6} | 4 Mbps | 6 Mbps | 10 Mbps | 20 Mbps |
| Maximum HDX CCUs ⁷ | 40 | 60 | 100 | 200 |
| Maximum accelerated TCP sessions ⁸ | 10,000 | 10,000 | 10,000 | 10,000 |

³Cloud server types are the minimum recommended server size to support the listed performance numbers for each model.

⁴Total encrypted throughput refers to total amount of bandwidth that the appliance model is licensed for, both upstream and downstream, and is based on AES-128 encryption.

⁵Only outbound WAN traffic is counted against the licensed bandwidth. Inbound QoS and/or unaccelerated traffic does not count against the licensed bandwidth. Total inbound traffic should not exceed this threshold.

⁶Some protocols (for example ICA) can limit the processing capacity of the appliance before the licensed bandwidth is reached.

⁷User count is based upon a medium-level workload as defined by Login VSI and Virtual Desktops/Apps advanced encryption security. User count is limited by link bandwidth and TCP session counts. No user count is enforced. Published numbers are for guidance purposes only.

⁸TCP session count will be reduced by active HDX sessions. No session count is enforced. Published numbers are for guidance purposes.

| WANOP Edition appliances | | | | | | | | |
|---|--------------|--------------|-------------|-------------|--------------|-------------|-------------|-------------|
| Appliance | 5100-WANOP | | 4100-WANOP | | | 3000-WANOP | | |
| Model | 5100-1500-WO | 5100-2000-WO | 4100-310-WO | 4100-500-WO | 4100-1000-WO | 3000-050-WO | 3000-100-WO | 3000-155-WO |
| Optimized WAN capacity ^{9,10} | 1.5 Gbps | 2 Gbps | 310 Mbps | 500 Mbps | 1 Gbps | 50 Mbps | 100 Mbps | 155 Mbps |
| QoS/unaccelerated throughput limit ⁹ | 2 Gbps | 4 Gbps | 500 Mbps | 1 Gbps | 2 Gbps | 500 Mbps | 500 Mbps | 500 Mbps |
| Maximum HDX CCUs ¹¹ | 3,500 | 5,000 | 750 | 1,200 | 2,500 | 300 | 400 | 500 |
| Maximum accelerated TCP sessions ¹² | 120,000 | 160,000 | 40,000 | 60,000 | 120,000 | 50,000 | 50,000 | 50,000 |
| Concurrent Citrix SD-WAN client plug-ins | 3,600 | 4,800 | 1,100 | 1,800 | 3,600 | 750 | 1,000 | 1200 |
| Video caching | | | | | | • | • | • |
| WCCP clustering | • | • | • | • | • | • | • | • |
| Networking Cloud Connector Group mode | • | • | • | • | • | • | • | • |
| Appliance | 2000-WANOP | | | 1000-WANOP | | | | |
| Model | 2000-010-WO | 2000-020-WO | 2000-050-WO | 1000-006-WO | 1000-010-WO | 1000-020-WO | | |
| Optimized WAN capacity ^{9,10} | 10 Mbps | 20 Mbps | 50 Mbps | 6 Mbps | 10 Mbps | 20 Mbps | | |
| QoS/unaccelerated throughput limit ⁹ | 200 Mbps | | | 50 Mbps | | | | |
| Maximum HDX CCUs ¹¹ | 100 | 200 | 300 | 60 | 100 | 200 | | |
| Maximum accelerated TCP sessions ¹¹ | 20,000 | 20,000 | 20,000 | 10,000 | 10,000 | 10,000 | | |
| Concurrent Citrix SD-WAN client plug-ins | 100 | 200 | 750 | | | | | |
| Video caching | • | • | • | • | • | • | | |
| WCCP clustering | • | • | • | • | • | • | | |
| Networking Cloud Connector | | | | | | | | |
| Group mode | • | • | • | • | • | • | | |
| Appliance | 800-WANOP | | | | | | | |
| Model | 800-002-WO | | 800-006-WO | | 800-010-WO | | | |
| Optimized WAN capacity ^{9,10} | 2 Mbps | | 6 Mbps | | 10 Mbps | | | |
| QoS/unaccelerated throughput limit ⁹ | 50 Mbps | | 50 Mbps | | 50 Mbps | | | |
| Maximum HDX CCUs ¹¹ | 20 | | 60 | | 100 | | | |
| Maximum accelerated TCP sessions ¹² | 10,000 | | 10,000 | | 10,000 | | | |
| Concurrent Citrix SD-WAN client plug-ins | | | | | | | | |
| Video caching | • | | • | | • | | | |
| WCCP clustering | • | | • | | • | | | |
| Networking Cloud Connector | | | | | | | | |
| Group mode | • | | • | | • | | | |

⁹Only outbound WAN traffic is counted against the licensed bandwidth. Inbound QoS and/or unaccelerated traffic does not count against the licensed bandwidth. Total inbound traffic should not exceed this threshold.

¹⁰Some protocols (for example ICA) can limit the processing capacity of the appliance before the licensed bandwidth is reached.

¹¹User count is based upon a medium-level workload as defined by Login VSI and Virtual Desktops/Apps advanced encryption security. User count is limited by link bandwidth and TCP session counts. No user count is enforced. Published numbers are for guidance purposes only.

¹²TCP session count will be reduced by active HDX sessions. No session count is enforced. Published numbers are for guidance purposes.

WANOP Edition virtual appliances

| Appliance | VPX | | | | | | | |
|--|---|--|-----------|-----------|-----------|------------|---|--|
| Model | VPX 2-WO | VPX 6-WO | VPX 10-WO | VPX 20-WO | VPX 50-WO | VPX 100-WO | VPX 200-WO | |
| Optimized WAN capacity ^{17,18} | 2 Mbps | 6 Mbps | 10 Mbps | 20 Mbps | 50 Mbps | 100 Mbps | 200 Mbps | |
| QoS/unaccelerated bandwidth limit | 15 Mbps | 50 Mbps | 75 Mbps | 150 Mbps | 250 Mbps | 250 Mbps | 300 Mbps | |
| Maximum HDX CCUs ¹⁹ | 20 | 60 | 100 | 200 | 300 | 400 | 500 | |
| Maximum accelerated TCP sessions ¹² | 5,000 | 5,000 | 5,000 | 10,000 | 10,000 | 20,000 | 30,000 | |
| Concurrent Citrix SD-WAN client plug-ins | 20 | 60 | 100 | 200 | 300 | 400 | 500 | |
| Video caching | • | • | • | • | • | | | |
| WCCP clustering | | | | | • | • | • | |
| Networking Cloud Connector ²¹ | • | • | • | • | • | • | • | |
| Group mode | | | | | | | | |
| Hypervisor | Citrix Hypervisor 5.5 - 6.2, Hyper-V 2008R2SP1 - 2012, ESX/ESXi 4.1-6.0 | | | | | | | |
| Processor | Dual core (quad core recommended) Intel VTx or AMD-V 64-bit x86 ²² | | | | | | | |
| Memory | 6 GB | | | | | 8 GB | 16 GB | |
| Virtual CPU | 1 x Citrix Hypervisor & 2 x VMware vSphere (>2.33GHz) | 2-4 x Citrix Hypervisor, Hyper-V & VMware vSphere (>2.33GHz) | | | | | 2-4 x Citrix Hypervisor, Hyper-V & VMware vSphere (~3.0GHz) | |
| Hard drive ²³ | 100 GB | 100 GB | 250 GB | 250 GB | 250 GB | 500 GB | 500 GB | |
| Network interface | 2 virtual NICs | | | | | | | |

¹⁷Only outbound WAN traffic is counted against the licensed bandwidth. Inbound QoS and/or unaccelerated traffic does not count against the licensed bandwidth. Total inbound traffic should not exceed this threshold.

¹⁸Some protocols (for example ICA) can limit the processing capacity of the appliance before the licensed bandwidth is reached.

¹⁹User count is based upon a medium level workload as defined by Login VSI and Virtual Desktops/Apps advanced encryption security. User count is limited by link bandwidth and TCP session counts. No user count is enforced. Published numbers are for guidance purposes only.

²⁰TCP session count will be reduced by active HDX sessions. No session count is enforced. Published numbers are for guidance purposes.

²¹For Citrix SD-WAN appliances, the Citrix Networking Cloud Connector is delivered as a separate software appliance.

²²The VPX images are qualified to run on Intel processors only.

²³For best performance, use solid state drives or high IOPs storage devices.

| Hardware specifications | | | | | |
|---|---|---|---------------------------------------|---------------------------------------|---|
| Appliance | 5100-SE | 5100-WO | 4100-SE | 4100-WO | 3000-WO |
| Storage | | | | | |
| Total disk space | 2 TB (HDD) | 6.8 TB (HDD) | 2TB (HDD) | 5.2 TB (HDD) | 2.4 TB |
| Compression history (SSD) | N/A | 4.3 TB | N/A | 2.8 TB | 1.5 TB |
| RAM | 128 GB | 128 GB | 96 GB | 96 GB | 32 GB |
| Network interfaces²⁴ | | | | | |
| Fail-to-wire | 4 x 10GBase-SR | 4 x 10GBase-SR | 2 x 10GBase-SR 4 x 1000Base-TX | 2 x 10GBase-SR 4 x 1000Base-TX | 6 x 1000Base-TX -or- 4 x 1000Base-SX |
| Non-Fail-to-wire | 4 x 10G/1G SFP+ | 4 x 10G/1G SFP+ | 4 x 10G/1G SFP+ | 4 x 10G/1G SFP+ | |
| Management | 2 x 1000Base-TX | 2 x 1000Base-TX | 2 x 1000Base-TX | 2 x 1000Base-TX | 2 x 1000Base-TX |
| Mechanical | | | | | |
| Rack units | 2U (3.5 inches / 8.90 cm) | | | | 1U (1.75 inches/4.45 cm) |
| Rack options | EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets | | | | |
| System depth | 28"/72 cm | 28"/72 cm | 28"/72 cm | 28"/72 cm | 24" (63.5 cm) |
| System weight | 60 lbs (27.2 kg) | 60 lbs (27.2 kg) | 60 lbs (27.2 kg) | 60 lbs (27.2 kg) | 33 lbs (15 kg) |
| Shipping dimensions | 36.5" x 24.5" by 11" (94 x 63 x 28 cm) | 36.5" x 24.5" by 11" (94 x 63 x 28 cm) | 36.5 X 24.5 X 11 (94 x 63 x 28 cm) | 36.5 X 24.5 X 11 (94 x 63 x 28 cm) | 32" x 23.5" x 7.5" (81.5 x 59.7 x 19.1 cm) |
| Shipping weight | 69 lbs (31.3 kg) | 69 lbs (31.3 kg) | 69 lbs (31.3 kg) | 69 lbs (31.3 kg) | 40 lbs (18.1 kg) |
| Power, environmental, and regulatory | | | | | |
| Power supplies | Dual Redundant, Hot Swappable | | | | Single (optional dual redundant) |
| Wattage (Max) | 1000W | 1000W | 1000W | 1000W | 450W (900W w/redundant PSU) |
| Input voltage / frequency ranges | 100-240 VAC, 47-63 Hz | 100-240 VAC, 47-63 Hz | 100-240VAC, 47-63 Hz | 100-240 VAC, 47-63 Hz | 100-240 VAC, 50-60 Hz |
| Input current | 9.0-4.5A | 9.0-4.5A | 7.0-3.5A | 7.0-3.5A | 2.5-1.0A |
| Operating temperature | 32-104 F (0-40 C) | | | | |
| Operating altitude | 0-4921 ft. (0-1500M) | | | | |
| Storage temperature | 14F to 140F (-10C to 60C) | | | | |
| Allowed relative humidity | 20%-80%, non-condensing | 20%-80%, non-condensing | 20%-80%, non-condensing | 20%-80%, non-condensing | 5%-95%, non-condensing |
| Safety certifications | CSA | CSA | CSA | CSA | UL, TUV-C |
| Electromagnetic emissions, safety and environmental | FCC (Part 15 Class A), CCC, KCC, NOM, CITC, EAC, DoC, CE, VCCI, RCM | | | | |
| Environmental compliance | RoHS, WEEE | | | | |
| Citrix compliance regulatory model | 2U1P1D | 2U1P1D | 2U1P1B | 2U1P1B | NS 6xSFP 6xCU |

²⁴Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

Hardware specifications

| Appliance | 2100-SE/PE | 2000-WO | 1100-SE/PE | 1000-SE/PE/WO | 800-WO |
|--|---|---|--|---|---|
| Storage | | | | | |
| Total disk space (SSD) | 720 GB (SSD) | 600 GB | 480 GB | 300 GB | 240 GB |
| Compression history (SSD) | SE-N/A PE-480 GB | 275 GB | SE-N/A PE-148 GB | 148 GB | 80 GB |
| RAM | 32GB | 32 GB | 24 GB | 24 GB | 8 GB |
| Network interfaces²⁴ | | | | | |
| Fail-to-wire | 4 x 1000Base-TX | | 4x 10/100/1000BaseTX | 4 x 1000Base-TX | |
| Non-Fail-to-wire | 4 x 1GE SFP | | 2x 10/100/1000Base-TX, 2 x Flexible ports (SFP or 10/100/1000 Base-TX), 2 x PoE | - | |
| Management interfaces | 1 x 1000Base-TX | | 1 x 1000Base-TX | 2 x 1000Base-TX | |
| Mechanical | | | | | |
| Rack units | 1RU (1.75 inches/4.45 cm) | | | | |
| Rack options | EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets | | | | |
| System depth | 24" (63.5 cm) | 24" (63.5 cm) | 9.8" (25 cm) | 10.5" (26.7 cm) | 10.5" (26.7 cm) |
| System weight | 26 lbs (11.8 kg) | 32 lbs (14.6 kg) | 4.5 lbs (2.04 Kg) | 8 lbs (3.63 kg) | 8 lbs (3.63 kg) |
| Shipping dimensions | 33" x 24" x 8" (76.2 x 61.0 x 20.3 cm) | 32" x 23.5" x 7.5" (81.5 x 59.7 x 19.1 cm) | 9.8" x 9.8" x 1.7" (25cm x 25cm x 4.5cm) | 25.5" x 6.1" x 18.5" (64.8 x 15.5 x 47.0 cm) | 25.5" x 6.1" x 18.5" (64.8 x 15.5 x 47.0 cm) |
| Shipping weight | 40 lbs (18.1 kg) | 39 lbs (17.8 kg) | 7.5 lbs (3.40 Kg) | 14.0 lbs (6.35 kg) | 14.0 lbs (6.35 kg) |
| Power, environmental, and regulatory | | | | | |
| Power supplies | Single(optional dual redundant) | Single | Single(optional dual redundant) | Single | Single |
| Wattage (Max) | 450W | 300W | 96.8W | 200W | 200W |
| Input voltage/frequency ranges | 100-240 VAC, 50-60 Hz | | | | |
| Input current | 3.4-1.7A | 1.5 - 0.6A | 2A | 2.6A Max | 2.6A Max |
| Operating temperature | 32F to 104F (0C to 40C) | | | | |
| Operating altitude | 0-4921 ft. (0-1500M) | | | | |
| Storage temperature | 14F to 140F (-10C to 60C) | | -4F to 140F (-20C to 60C) | | |
| Allowed relative humidity | 20%-80% non-condensing | 5%-95% non-condensing | | | |
| Safety certifications | CSA | UL, TUV-C | UL | UL, TUV-C | |
| Electromagnetic emissions, safety and environmental | FCC (Part 15 Class A), CCC, KCC, FCC (Part 15, Class B) for 1100 SE/PE only, NOM, CITC, EAC, DoC, CE, VCCI, RCM | | | | |
| Environmental compliance | RoHS, WEEE | | | | |
| Citrix compliance regulatory model | 1U1P1A | NS 6xCu | SDW-1100 | CB 504-2 | |

²⁴Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

Hardware specifications

| Appliance | 410-SE | 210-SE | 210-LTE-SE (R1/R2/RC) |
|---|--|---|---|
| Storage | | | |
| Total disk space (SSD) | 60 GB | 64GB (mSATA) | 64GB (mSATA) |
| Compression history (SSD) | N/A | N/A | N/A |
| RAM | 8 GB | 4 GB | 4 GB |
| Network interfaces²⁴ | | | |
| Fail-to-wire | 6 x 1000Base-TX | 2x 10/100/1000 Ethernet with Bypass RJ45 | 2x 10/100/1000 Ethernet with Bypass RJ45 |
| Non-Fail-to-wire | - | 1x 10/100/1000 Ethernet RJ45 2 x flexible ports (10/100/1000 Ethernet RJ45 or 1GE SFP) | 2 x flexible ports (10/100/1000 Ethernet RJ45 or 1GE SFP) |
| Management interfaces | 1 x 1000Base-TX | 1x 10/100/1000 RJ45 | 1x 10/100/1000 RJ45 |
| Integrated LTE | - | - | 1 X LTE Modem ²⁵ |
| Mechanical | | | |
| Rack units | 1RU (1.75 inches/4.45 cm) | 1RU (1.75 inches/4.45 cm) | 1RU (1.75 inches/4.45 cm) |
| Rack options | EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets | EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets | EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets |
| System depth | 14" (35 cm) | 6.9" | 6.9" |
| System weight | 8.5 lbs (3.87 kg) | 2.75 lbs (1.25 kg) | 3.15 lbs (1.42 kg) |
| Shipping dimensions | 26" x 6.5" x 18.5" (66.1 x 16.6 x 47.0 cm) | 17.5" X 12" X 2.75" (44.5 x 30.5 x 7.0 cm) | 17.5" X 12" X 2.75" (44.5 x 30.5 x 7.0 cm) |
| Shipping weight | 13.5 lbs (6.14 kg) | 4.6 lbs (2.09 kg) | 5.0 lbs (2.27 kg) |
| Power, environmental, and regulatory | | | |
| Power supplies | Single | Single | Single |
| Wattage (Max) | 200W | 45W external | 45W external |
| Input voltage/frequency ranges | 100-240 VAC, 50-60 Hz | 100-240VAC, 47-63Hz | 100-240VAC, 47-63Hz |
| Input current | 3-1.5A | 4.0-2.1A | 4.0-2.1A |
| Operating temperature | 32F to 104F (0C to 40C) | 32F to 104F (0C to 40C) | 32F to 104F (0C to 40C) |
| Operating altitude | 0-4921 ft. (0-1500M) | 0-4921 ft. (0-1500M) | 0-4921 ft. (0-1500M) |
| Storage temperature | 14F to 140F (-10C to 60C) | 14F to 140F (-10C to 60C) | 14F to 140F (-10C to 60C) |
| Allowed relative humidity | 20%-80% non-condensing | 5%-90%, non-condensing | 5%-90%, non-condensing |
| Safety certifications | CSA | UL | UL |
| EMC | FCC (Part 15 Class A), CCC, KCC, NOM, CITC, EAC, CE, VCCI, RCM, RCM, Anatel, NTRA, BIS, MOC, ICASA, BSMI | FCC (Part 15 Class B), CE, Anatel, BIS, BSMI, CCC, CITC, EAC, ICASA, KCC, RCM, VCCI | FCC (Part 15 Class A), CE, Anatel, BIS, BSMI, CCC, CITC, EAC, ICASA, KCC, RCM, VCCI, NAL,SSRC ²⁶ |
| Environmental compliance | RoHS, WEEE, REACH | RoHS, WEEE, REACH | RoHS, WEEE, REACH |
| Citrix compliance regulatory model | 512-2 | SDW-210 | NS-SDW-210-LTE-R1, NS-SDW-210-LTE-R2 and NS-SDW-210-LTE-RC |

²⁴Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

²⁵210-LTE-R1: Primarily for Americas and EMEA regions. Exceptions apply for some countries. Bands Supported: B1-B5, B7, B12, B13, B20, B25, B26, B29, B30, B41 | 210-LTE-R2: Primarily for APAC Region. Exceptions apply for some countries. Bands Supported: B1, B3, B5, B7, B8, B18, B19, B21, B28, B38-B41 | 210-LTE-RC: For China only. Bands Supported: B1, B3, B5, B7, B8, B18, B19, B21, B28, B38, B40, B41 | Please contact your Citrix sales representative for more information.

²⁶210-LTE-RC: EMC Certifications include CCC, NAL, SSRC – FCC (Part 15 Class A), CE, CITC, EAC, ENACOM, IFT 210-LTE-R2: EMC certifications include – FCC (Part 15 Class A), CE, Anatel, BIS, BSMI, CITC, EAC, ICASA, MIC, NTC, RAA, RCM



Enterprise Sales

North America | 800-424-8749
Worldwide | +1 408-790-8000

Locations

Corporate Headquarters | 851 Cypress Creek Road Fort Lauderdale, FL 33309 United States
Silicon Valley | 4988 Great America Parkway Santa Clara, CA 95054 United States

Copyright© 2019 Inc. All rights reserved. Citrix, the Citrix logo, and other marks appearing herein are property of Citrix Systems, Inc. and/or one or more of its subsidiaries, and may be registered with the U.S. Patent and Trademark Office and in other countries. All other marks are the property of their respective owner/s.